



NIJ 06 LEVEL IIIA - GPAlIIIA-2

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT
LEVEL
IIIA

NIJ
0101.06
CERTIFIED



Country of Certification:	Canada
Ballistic Standard:	NIJ 0101.06
NIJ Model:	GPAlIIIA-2
Threat Level:	IIIA
Areal Density:	1.0 lb/ft ² (4.88 kg/m ²)
Thickness:	0.35" (9.0 mm)
Composition:	Kevlar®/Spectra® Shield/Dyneema®
Stitching:	Shoulder Tack/X Stitch
Ballistic Package:	200 Denier Ripstop Nylon Cover Urethane Backed Ultrasonically Welded Seams Patented Internal Desiccant
Ply Count:	30
NIJ 0101.06 Size Range:	C1 to C5

DuPont™
KEVLAR®

BALLISTIC PERFORMANCE AT CERTIFICATION

.357 Sig New V50	1805 ft/s (550 m/s)	.44 Mag New V50	1594 ft/s (486 m/s)
.357 Sig Conditioned V50	1905 ft/s (581 m/s)	.44 Mag Conditioned V50	1609 ft/s (490 m/s)
.357 Sig BFS	28.2 mm	.44 Mag BFS	39.5 mm
.357 Sig New RPI	1805.0	.44 Mag New RPI	1594.0
.357 Sig Conditioned RPI	1905.0	.44 Mag Conditioned RPI	1609.0

EXAMPLE CARRIERS



Concealable



**Premium
Concealable**



Clean Front



**Tactical
Response**



Shirt Front



Tactical Patrol

124 Fourth Avenue | Arnprior, ON K7S 0A9
TOLL FREE (888) 997-9923 | FAX (613) 623-6169
www.pacsafety.com

