

**NIJ
0101.06
CERTIFIED**



Country of Certification:	Canada
Ballistic Standard:	NIJ 0101.06
NIJ Model:	UG2F06
Threat Level:	II
Areal Density:	0.82 lb/ft ² (4.00 kg/m ²)
Thickness:	0.18" (4.6 mm)
Composition:	Spectra® Shield /Goldshield® Hybrid
Stitching:	Shoulder Tacks, bottom stitch
Ballistic Panel Cover:	200 Denier Nylon Cover Polyurethane Backed Ultrasonically Welded Seams Patented Internal Desiccant
Ply Count:	31
NIJ 0101.06 Size Range:	C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1748 fps. (533 m/s)	.357 Mag New V50	1648 fps. (502 m/s)
9mm Conditioned V50	1683 fps. (513 m/s)	.357 Mag Conditioned V50	1625 fps. (495 m/s)
9mm BFS	29.8 mm	.357 Mag BFS	34.4 mm
9mm New RPI	2106.0	.357 Mag New RPI	1985.5
9mm Conditioned RPI	2027.7	.357 Mag Conditioned RPI	1957.8

EXAMPLE CARRIERS



Concealable



**Premium
Concealable**



Clean Front



**Tactical
Response**



Shirt Front



Tactical Patrol

124 Fourth Avenue | Arnprior, ON K7S 0A9
TOLL FREE (888) 997-9923 | FAX (613) 623-6169
www.pacsafety.com