

# LITE X

NIJ 06 LEVEL II - UG062XG-F  
NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT  
LEVEL  
II

DuPont™  
**KEVLAR®**



**NIJ**  
**0101.06**  
**CERTIFIED**

Country of Certification:	CANADA
Ballistic Standard:	NIJ 0101.06
NIJ Model:	UG062XG-F
Gender:	Female
Threat Level:	II
Areal Density:	0.96 lb/ft <sup>2</sup> (4.68 kg/m <sup>2</sup> )
Thinness:	0.24" (6.0 mm)
Composition:	Kevlar® Comfort XLT™ / Goldflex® Hybrid
Stitching:	1"x1" Diamond Quilt in Woven Fabric, Shoulder Box and Waist Tack
Ballistic Package:	70 denier Ripstop Cover Nylon Urethane Backed Heat Sealed Seams Patented Internal Desiccant
Ply Count:	28
NIJ 0101.06 Size Range:	C1 to C5

## BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1716 fps. (523 m/s)	.357 Mag New V50	1646 fps. (502 m/s)
9mm Conditioned V50	1640 fps. (500 m/s)	.357 Mag Conditioned V50	1623 fps. (495 m/s)
9mm Sig BFS	31.2 mm	.357 Mag BFS	32.6 mm
9mm New RPI	1787.5	.357 Mag New RPI	1714.6
9mm Conditioned RPI	1708.3	.357 Mag Conditioned RPI	1690.6

## EXAMPLE CARRIERS



Concealable



Tactical Outer Carrier



Tactical Response Carrier



Shirt Front Carrier



Clean Front Carrier

124 Fourth Avenue | Arnprior, ON K7S 0A9  
TOLL FREE (888) 997-9923 | FAX (613) 623-6169  
[www.pacsafety.com](http://www.pacsafety.com)