

LITE X

NIJ 06 LEVEL IIIA - UG3AKXP

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT
LEVEL
IIIA

DuPont™
KEVLAR®

NIJ
0101.06
CERTIFIED



Country of Certification:	CANADA
Ballistic Standard:	NIJ 0101.06
NIJ Model:	UG3AKXP
Threat Level:	IIIA
Areal Density:	1.26 lb/ft ² (6.16 kg/m ²)
Thinness:	0.28" (7.1 mm)
Composition:	Kevlar® Comfort XLT™ / Kevlar® XP™ Hybrid
Stitching:	1"x1" Diamond Quilt in Woven Fabric, Shoulder Box and Waist Tack
Ballistic Package:	200 denier Ripstop Cover Nylon Urethane Backed Heat Sealed Seams Patented Internal Desiccant
Ply Count:	25
NIJ 0101.06 Size Range:	C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

.357 Sig New V50	1914 fps. (583 m/s)	.44 Mag New V50	1725 fps. (526 m/s)
.357 Sig Conditioned V50	1890 fps. (576 m/s)	.44 Mag Conditioned V50	1743 fps. (531 m/s)
.357 Sig BFS	27.0 mm	.44 Mag BFS	36.4 mm
.357 Sig New RPI	1519.0	.44 Mag New RPI	1369.0
.357 Sig Conditioned RPI	1500.0	.44 Mag Conditioned RPI	1383.3

EXAMPLE CARRIERS



Concealable



Premium
Concealable



Clean Front



Tactical
Response



Shirt Front



Tactical Patrol

124 Fourth Avenue | Arnprior, ON K7S 0A9
TOLL FREE (888) 997-9923 | FAX (613) 623-6169
www.pacsafety.com

PSP™
Pacific Safety Products Inc.