

LITE X

NIJ 06 LEVEL IIIA - UG3AKXP-F
NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT
LEVEL
IIIA

DuPont™
KEVLAR®



NIJ
0101.06
CERTIFIED

Country of Certification:	CANADA
Ballistic Standard:	NIJ 0101.06
NIJ Model:	UG062XG-F
Gender:	Female (Structured Design)
Threat Level:	IIIA
Areal Density:	1.26 lb/ft ²
Thickness:	0.31"
Composition:	Kevlar® Comfort XLT™ / Kevlar® XP™ Hybrid
Stitching:	1"x1" Diamond Quilt in Woven Fabric, Shoulder Box and Waist Tack, Front Panel Molded Bias Construction
Ballistic Package:	70 denier Ripstop Cover Nylon Urethane Backed Ultrasonically Welded Seams Patented Internal Desiccant
Ply Count:	31
NIJ 0101.06 Size Range:	C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

.357 Sig New V50	1919 fps.	.44 Mag New V50	1756 fps.
.357 Sig Conditioned V50	1918 fps.	.44 Mag Conditioned V50	1661 fps.
.357 Sig BFS	28.3 mm	.44 Mag BFS	38.4 mm
.357 Sig New RPI	1523.0	.44 Mag New RPI	1393.7
.357 Sig Conditioned RPI	1522.2	.44 Mag Conditioned RPI	1318.3

EXAMPLE CARRIERS



Concealable



Tactical Outer
Carrier



Tactical Response
Carrier



Shirt Front
Carrier



Clean Front
Carrier

124 Fourth Avenue | Arnprior, ON K7S 0A9
TOLL FREE (888) 997-9923 | FAX (613) 623-6169
www.pacsafety.com