

**NIJ  
0101.06  
CERTIFIED**



Country of Certification:	Canada
Ballistic Standard:	NIJ 0101.06
NIJ Model:	P3AHL2DX
Threat Level:	IIIA
Areal Density:	1.45 lb/ft <sup>2</sup> (7.08 kg/m <sup>2</sup> )
Thickness:	0.34" (8.6 mm)
Composition:	100% Aramid Laminate
Stitching:	4"x 4" Diamond Quilt, Shoulder Box
Ballistic Panel Cover:	200 denier Ripstop Cover Nylon Polyurethane Backed Ultrasonically Welded Seams Patented Internal Desiccant
Ply Count:	12
NIJ 0101.06 Size Range:	C2 to C5

#### BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1739 ft/s (530 m/s)	.357 Mag New V50	1631 ft/s (497 m/s)
9mm Conditioned V50	1764 ft/s (538 m/s)	.357 Mag Conditioned V50	1561 ft/s (476 m/s)
9mm BFS	28.8 mm	.357 Mag BFS	38.3 mm
9mm New RPI	1199.3	.357 Mag New RPI	1124.8
9mm Conditioned RPI	1216.6	.357 Mag Conditioned RPI	1076.6

#### EXAMPLE CARRIERS



**Concealable**



**Premium  
Concealable**



**Clean Front**



**Tactical  
Response**



**Shirt Front**



**Tactical Patrol**

124 Fourth Avenue | Arnprior, ON K7S 0A9  
TOLL FREE (888) 997-9923 | FAX (613) 623-6169  
[www.pacsafety.com](http://www.pacsafety.com)