



# LITEX II LX02

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT  
LEVEL

II

**NIJ**  
0101.06  
CERTIFIED



**Country of Certification:** Canada  
**Ballistic Standard:** NIJ 0101.06  
**NIJ Model:** GPBII-3  
**Series:** LX02  
**Threat Level:** II  
**Areal Density:** 0.90 lb/ft<sup>2</sup> (4.39 kg/m<sup>2</sup>)  
**Thinness:** 0.22 in. (5.6 mm)  
**Composition:** Twaron®/Goldflex® Hybrid  
**Stitching:** Diamond Quilt, Perimeter Stitch, Shoulder Tacks, Bottom Stitch

**Ballistic Package:** 200 denier Nylon  
Polyurethane Backed  
Ultra-Sonic Welded Seams  
Patented Internal Desiccant

**Ply Count:** 21  
**NIJ 0101.06 Size Range:** C1 to C5

## BALLISTIC PERFORMANCE AT CERTIFICATION

<b>9mm New V50</b>	1683 fps. (513 m/s)	<b>.357 Mag New V50</b>	1644 fps. (501 m/s)
<b>9mm Conditioned V50</b>	1614 fps. (492 m/s)	<b>.357 Mag Conditioned V50</b>	1613 fps. (492 m/s)
<b>9mm BFS</b>	30.8 mm	<b>.357 Mag BFS</b>	33.8 mm
<b>9mm New RPI</b>	1870.0	<b>.357 Mag New RPI</b>	1826.7
<b>9mm Conditioned RPI</b>	1793.3	<b>.357 Mag Conditioned RPI</b>	1792.2

**SPECIAL THREAT TESTED: 9MM 127GR SXT AND 357 SIG 125GR GDHP**

## OPTIONAL CARRIERS



Concealable Carrier



Premium Concealable Carrier



Tactical Response Carrier



Uniform Shirt Carrier



Clean Front Carrier



Tactical Outer Carrier

124 Fourth Avenue | Arnprior, ON K7S 0A9  
TOLL FREE (888) 997-9923 | FAX (888) 969-5469  
[www.pacsafety.com](http://www.pacsafety.com)