



LITEX IIIA LX02

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT
LEVEL
IIIA

NIJ
0101.06
CERTIFIED



Country of Certification: Canada
Ballistic Standard: NIJ 0101.06
NIJ Model: GPBIIIA-2
Series: LX02
Threat Level: IIIA
Areal Density: 1.16 lb/ft² (5.66 kg/m²)
Thinness: 0.27 in. (6.9 mm)
Composition: Twaron®/Goldflex® Hybrid
Stitching: Diamond Quilt, Perimeter Stitch, Shoulder Tacks, Bottom Stitch
Ballistic Package: 200 denier Nylon
 Polyurethane Backed
 Ultra-Sonic Welded Seams
 Patented Internal Desiccant
Ply Count: 28
NIJ 0101.06 Size Range: C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

.357 Sig New V50	1856 fps. (566 m/s)	.44 Mag New V50	1643 fps. (501 m/s)
.357 Sig Conditioned V50	1766 fps. (538 m/s)	.44 Mag Conditioned V50	1560 fps. (475 m/s)
.357 Sig BFS	28.9 mm	.44 Mag BFS	39.0 mm
.357 Sig New RPI	1600.0	.44 Mag New RPI	1416.4
.357 Sig Conditioned RPI	1522.4	.44 Mag Conditioned RPI	1344.8

SPECIAL THREAT TESTED: 9MM 127GR SXT AND 357 SIG 125GR GDHP AND FN 5.7X28MM 40 GR SS197SR

OPTIONAL CARRIERS



Concealable
Carrier



Premium Concealable
Carrier



Tactical Response
Carrier



Uniform
Shirt Carrier



Clean Front
Carrier



Tactical Outer
Carrier

124 Fourth Avenue | Arnprior, ON K7S 0A9
 TOLL FREE (888) 997-9923 | FAX (888) 969-5469
www.pacsafety.com