



# TYPE II - UG2F06-F

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT LEVEL

II



**NIJ  
0101.06  
CERTIFIED**

Country of Certification:	Canada
Ballistic Standard:	NIJ 0101.06
NIJ Model:	UG2F06-F
Threat Level:	II
Areal Density:	0.82 lb/ft <sup>2</sup> (4.00 kg/m <sup>2</sup> )
Thickness:	0.18" (4.6 mm)
Composition:	Spectra® Shield /Goldshield® Hybrid
Stitching:	Shoulder Tacks, bottom stitch Front Panel: Orthogonal Bias Construction
Ballistic Panel Cover:	70 Denier Nylon Cover Polyurethane Backed Ultra-Sonic Welded Seams Patented Internal Desiccant
Ply Count:	31
NIJ 0101.06 Size Range:	C1 to C5

### BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1591 fps. (485 m/s)	.357 Mag New V50	1575 fps. (480 m/s)
9mm Conditioned V50	1660 fps. (506 m/s)	.357 Mag Conditioned V50	1651 fps. (503 m/s)
9mm BFS	27.7 mm	.357 Mag BFS	30.7 mm
9mm New RPI	1916.9	.357 Mag New RPI	1897.6
9mm Conditioned RPI	2000.0	.357 Mag Conditioned RPI	1989.2

### EXAMPLE CARRIERS



Concealable



Tactical Outer Carrier



Tactical Response Carrier



Shirt Front Carrier



Clean Front Carrier

124 Fourth Avenue | Arnprior, ON K7S 0A9  
TOLL FREE (888) 997-9923 | FAX (613) 623-6169  
[www.pacsafety.com](http://www.pacsafety.com)

