



TALONX II/2 -TX02

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT LEVEL
II/2

DuPont™
KEVLAR®

NIJ
0101.06
CERTIFIED



Country of Certification:	CANADA
Ballistic Standard:	NIJ 0101.06
Stab Standard:	NIJ 0115.00
NIJ Model:	GPMII2-4
Series:	TX02
Ballistic Threat Level:	II
Stab Threat Level:	Spike 2
Areal Density:	1.1 lb/ft ² (5.37 kg/m ²)
Thickness:	0.34 in. (8.6 mm)
Composition:	Kevlar® Correctional/ Kevlar® KM2+™ Hybrid
Stitching:	Diamond Quilt, Top Stitch
Ballistic Package:	200 denier Nylon Cover, Polyurethane Backed, Ultra-Sonic Welded Seams Patented Internal Desiccant
Ply Count:	36
NIJ 010106 Size Range:	C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1618 ft/s (493 m/s)	.357 Mag New V50	1574 ft/s (480 m/s)
9mm Conditioned V50	1624 ft/s (495 m/s)	.357 Mag Conditioned V50	1542 ft/s (470 m/s)
9mm BFS	27.7 mm	.357 Mag BFS	31.3 mm
9mm New RPI	1470.9	.357 Mag New RPI	1430.9
9mm Conditioned RPI	1476.4	.357 Mag Conditioned RPI	1401.8

SPIKE RESISTANCE RATING

Protection Threat	Level 2	Energy Level 1 (E1)	24.3 ft-lbs/33 J
Protection Class	Spike	Energy Level 2 (E2)	36.9 ft-lbs/50 J

WARNING: This product is not intended to protect the wearer from commercially-made edged weapons or rifle fire.

EXAMPLE CARRIERS



Concealable



Premium
Concealable



Clean Front



Tactical
Response



Shirt Front



Tactical Patrol

124 Fourth Avenue | Arnprior, ON K7S 0A9
TOLL FREE (888) 997-9923 | FAX (613) 623-6169
www.pacsafety.com

